

Technical data

Refer to page 54 for electrical values

Rated working voltage:	max. 42 V / 250 V depending on connection
Rated working current:	max. 2 A
Protection class:	2, protective insulation 
Temperature resistance of sealing materials:	NBR -40°C ... +100°C
	EPDM -30°C ... +120°C
	FKM (in diaphragm pressure switch) -5°C ... +120°C
	FKM (in piston pressure switch) -15°C ... +120°C
	Silicone -40°C ... +120°C
	HNBR -30°C ... +120°C
Switching frequency:	200 / min.
Mechanical life expectancy:	1,000,000 cycles (for diaphragm pressure switches, life expectancy value only applies for switching pressures to max. 50 bar)
Pressure rise rate:	≤ 1 bar/ms
Hysteresis:	Average value 10 – 20 % (not adjustable)
Vibration resistance:	10 g / 5 – 200 Hz sine wave, DIN EN 60068-2-6
Shock resistance:	294 m/s ² ; 14 ms half sine wave, DIN EN 60068-2-6
Materials:	Housing material: zinc-plated steel Protective cap: anodised aluminium
Protection class:	IP67
Cable:	Standard length 2 m with wire end sleeves
Weight:	approx. 120 g

Options for 0240 / 0241

- Other cable lengths and plug-in systems
- Fixed switching point, factory-set, set point embossed on housing
- Alternative housing materials and connection threads
- Other sealing materials, such as silicone for diaphragm pressure switches

0240 / 0241

Diaphragm / piston pressure switches, hex 27

- Zinc-plated steel (CrVI-free)
- Overpressure safety up to 300 / 600 bar ¹⁾
- Switching point can also be adjusted during use
- Protection class 2, protective insulation 

p _{max.} in bar	Adjustment range in bar	Tolerance in bar at room temperature	Male thread	Order number
-----------------------------	----------------------------	---	-------------	--------------

0240 Diaphragm pressure switches

300 ¹⁾	0.3 – 1.5	± 0.2	G 1/4	0240 – 457 03 – X – 003
			NPT 1/8	0240 – 457 04 – X – 300
			NPT 1/4	0240 – 457 09 – X – 305
			7/16-20 UNF	0240 – 457 20 – X – 310
			9/16-18 UNF	0240 – 457 21 – X – 315
	1 – 10	± 0.5	G 1/4	0240 – 458 03 – X – 006
			NPT 1/8	0240 – 458 04 – X – 301
			NPT 1/4	0240 – 458 09 – X – 306
			7/16-20 UNF	0240 – 458 20 – X – 311
			9/16-18 UNF	0240 – 458 21 – X – 316
	10 – 20	± 1.0	G 1/4	0240 – 459 03 – X – 009
			NPT 1/8	0240 – 459 04 – X – 302
			NPT 1/4	0240 – 459 09 – X – 307
			7/16-20 UNF	0240 – 459 20 – X – 312
			9/16-18 UNF	0240 – 459 21 – X – 317
	20 – 50	± 2.0	G 1/4	0240 – 461 03 – X – 012
			NPT 1/8	0240 – 461 04 – X – 303
			NPT 1/4	0240 – 461 09 – X – 308
			7/16-20 UNF	0240 – 461 20 – X – 313
			9/16-18 UNF	0240 – 461 21 – X – 318

0241 Piston pressure switches

600 ¹⁾	50 – 150	± 5.0	G 1/4	0241 – 460 03 – X – 003
			NPT 1/8	0241 – 460 04 – X – 304
			NPT 1/4	0241 – 460 09 – X – 309
			7/16-20 UNF	0241 – 460 20 – X – 314
			9/16-18 UNF	0241 – 460 21 – X – 319

Seal material – Application areas

NBR	Hydraulic/machine oil, heating oil, air, nitrogen, etc.	1
EPDM	Brake fluid, hydrogen, oxygen, acetylene, etc.	2
FKM	Hydraulic fluids (HFA, HFB, HFD), petrol/gasoline, etc.	3
HNBR	Hydraulic/machine oil, ester-based bio-oils	9


Refer to page 64 for the temperature range and application thresholds of sealing materials.

Your order number:

024X – XXX XX – X – XXX

M.5

hex 24 / 27
Ready-wired



Contact assignment:

- 1 = Black
- 2 = Red
- 4 = White



¹⁾ Static value. Dynamic value is 30-50 % lower. Values pertain to the hydraulic/pneumatic part of the pressure switch.